

SENSE AMAZON WHITE MATT 350x1000



Class 1 Building Product Information Requirements Self-Assessment

Product Name: SENSE AMAZON WHITE MATT 350x1000

Product Identifier: AMAWH35X100

Product Description: A glazed ceramic tile with an matt finish and a water absorption rate of less than 16.00%.

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



BPIR COMPLIANT



Scope	Use
B2 Durability	See below Suitability table.
C3 Fire	The Building Code relating to fire ratings regulation and standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Not acceptable for use under D1/AS1
E3 Internal Moisture	Under E3 Tiles installed over a waterproof membrane using a nonporous Grouting system, are an acceptable solution.
G3 Food Preparation and Prevention from Contamination	As an Impervious and easy to clean Surface this range complies
G6 Airborne and Impact Sound	If required Tiles can form part of an acoustic system to comply with IIC and STC in conjunction with an approved third-party system.

Suitability	Residential	Light Commercial	Commercial	Industrial
Indoor Floor	-	-	-	-
Indoor Walls	✓	✓	✓	✓
Outdoor Floor	-	-	-	-
Outdoor Cladding	-	-	-	-
Frost Resistant	-	-	-	-
Swimming Pool Submerged	-	-	-	-
Swimming Pool Surround	-	-	-	-
Paving	-	-	-	-
Over Underfloor Heating	-	-	-	-
Commercial Kitchen Wall	-	-	-	-
Within 1.5m of a Plumbing Fixture or Fitting	✓	✓	✓	✓

Note – this building product is not subject to a warning or ban under section 26 of the Building Act 2004

Specifications	
CODE	AMAWH35X100
TILE SIZE (mm)	350x1000
THICKNESS (mm)	8
SUITABILITY	Wall
FINISH	Matt
CLASS	PEI Class 0: Glazed tiles in this class are wall tiles only and unsuitable for use on floors.
RECTIFIED	Yes
WEIGHT (kg)	4.49
COEFFICIENT OF FRICTION	
SLIP RATING	
TILES PER BOX	4
M2 PER BOX	1.40
PATTERNS/FACES	20
COUNTRY OF ORIGIN	Portugal

Building Code Clause and Contribution

B2 - Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source.

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

For D1 access routes, in most cases product-related compliance for access routes are slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed. Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious.

G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:

Tile Warehouse Approved



Importer Details:

Tile Warehouse Limited

Address: 286 Church Street, Onehunga, AKL 1061

NZBN: 9429041069448

Website: www.tilewarehouse.co.nz

Tender Specifications

Supply of ceramic wall and floor tiles

Product characteristics

Single Fired Wall Tiles

The white body product is composed of a mixture of quality clay with the addition of feldspar, quartz and kaolin. It is manufactured by dry pressing of atomized powder, with the application of enamel, and then sintered by industrial burning at temperatures above 1100°C.

The product is resistant to cracking, bending, impact, staining, chemical attack and thermal shock.

The Sense collection complies with the regulations required for top quality products in Europe according to EN 14411-L and internationally through ISO 13006-L.

Unglazed Porcelain Tiles (UGL)

Unglazed porcelain stoneware consists of a mixture of quality clay with the addition of feldspar, quartz and kaolin. It is manufactured by dry pressing of atomized powder and then sintered by industrial burning at temperatures above 1100°C.

The glazing level of the material makes it possible to obtain a compact, non-porous product, resistant to ice, bending, impact, staining, chemical attack and thermal shock.

The Sense collection complies with the regulations required for top quality products in Europe according to EN 14411-G and internationally through ISO 13006-G.

Quality and environmental certifications

The conservation of the product characteristics is guaranteed by the Quality Management System put into practice by Gres Panaria Portugal in its plants and certified in accordance with EN ISO 9001.

The collection is manufactured in plants with EN ISO 14001 certified Environmental Management Systems (internationally recognized standard) and EMAS (Regulation 1221/09 - eco-management and audit community system).

The collection helps to meet the criteria for obtaining LEED credits.

Antibacterial properties - PR()TECT

Thanks to Protect® antibacterial technology, the tiles in the Sense collection have continuous, effective and long-lasting protection against the proliferation of bacteria, tested and certified according to ISO 22196 and ASTM E3031.

Commercial description of the product			
Company	Love Ceramic Tiles		
Collection	Sense		
Colours	White, Beige, Light Grey, Grey, Anthracite		
Sizes	Wall tiles	35x100 RET.	35x70 RET.
	Wall tiles - Structures	35x100 RET. _ Amazon, Scratch	
	Floor tiles (UGL)	80x80 RET.	60x60 RET.
Finish - Surface	Wall tiles	Matt - Matt looking surface. Recommended for interior wall cladding.	
	Floor tiles (UGL)	Touch In&Out Anti-slip (AS)	
Finish - Edge	Rectified (RET), Non Rectified		
Thickness	Wall tiles	8mm _ 35x100 RET., 35x70 RET. 7mm _ 31x62	
	Wall tiles - Structures	Amazon 7,6-7,8mm Scratch 7,7-8,1mm Elevation 7,3-8,8mm Botanic 7,2-8,7mm	
	Floor tiles (UGL)	9mm _ 80x80 8mm _ 60x60, 30x60	



EMAS

ISO 9001 | ISO 14001

RECYCLED CONTENT

LEED

CE

CERTIF

ANTIBACTERIANO

GREENGUARD GOLD

EPD

Tender Specifications

Technical features

Product type: **Single Fired Wall Tiles**

According to: ISO 13006 - Annex L (Group BIII), EN 14411 - Annex L (Group BIII)

Technical features		Test method	Prescribed Value	Typical Value
Dimensions	Lenght and width	EN ISO 10545-2	Non Rect. $\pm 0,6\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,0$ mm	Conform
	Side straightness		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,5$ mm	Conform
	Rectangularity		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,5$ mm	Conform
	Warpage - Center and edge curvature		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,4\%$, max $\pm 1,8$ mm	Conform
	Warpage		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,4\%$, max $\pm 1,8$ mm	Conform
	Thickness		$\pm 10\%$, max $\pm 0,5$ mm	Conform
Water absorption (E)		EN ISO 10545-3	E > 10%	16%
Modulus of rupture		EN ISO 10545-4	≥ 12 N/mm ²	19 N/mm ²
Breaking strength (S)			S ≥ 600 N	700 N
Linear thermal expansion		EN ISO 10545-8	As indicated by manufacturer	$\alpha \leq 7,5 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$ Maximum value
Thermal shock resistance		EN ISO 10545-9	Required	Resistant
Crazing resistance		EN ISO 10545-11	Required	Resistant
Resistance against acids and alkalis		EN ISO 10545-13	As indicated by manufacturer	GLB
Resistance to household cleaning products			Minimum: GB	GA
Stain Resistance		EN ISO 10545-14	Minimum: class 3	4
Recomended joint		Rectified Indoor	-	Minimum 2 mm

It is guaranteed the compliance with the values required by norm EN 14411_Group BIII. Typical Value is merely indicative, which can vary from real data, and does not have the purpose of any trading proposal.



Tender Specifications

Technical features

Product type: **Unglazed Porcelain Tiles (UGL)**

According to: ISO 13006 - Annex G (Group Bla), EN 14411 - Annex G (Group Bla)

Technical features		Test method	Prescribed Value	Typical Value
Dimensions	Lenght and width	EN ISO 10545-2	Non Rect. $\pm 0,6\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,0$ mm	Conform
	Side straightness		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,5$ mm	Conform
	Rectangularity		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,3\%$, max $\pm 1,5$ mm	Conform
	Warpage		Non Rect. $\pm 0,5\%$, max $\pm 2,0$ mm Rect. $\pm 0,4\%$, max $\pm 1,8$ mm	Conform
	Thickness		$\pm 5\%$ max $\pm 0,5$ mm	Conform
Water absorption (E)		EN ISO 10545-3	$E \leq 0,5\%$	0,1%
Modulus of rupture		EN ISO 10545-4	≥ 35 N/mm ²	50 N/mm ²
Breaking strength (S)			$S \geq 1300$ N	2500 N
Abrasion resistance		EN ISO 10545-6	≤ 175 mm ³	139mm ³
Linear thermal expansion		EN ISO 10545-8	As indicated by manufacturer	$\alpha \leq 7,5 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$
Thermal shock resistance		EN ISO 10545-9	Required	Resistente
Crazing resistance		EN ISO 10545-11	Required	Resistente
Frost resistance		EN ISO 10545-12	Required	Resistente
Resistance against acids and alkalis		EN ISO 10545-13	As indicated by manufacturer	ULB
Resistance to household cleaning products			Minimum: UB	UA
Stain Resistance		EN ISO 10545-14	As indicated by manufacturer	4
Slip Resistance	DIN EN 16165 _ Annex B	As indicated by manufacturer	R10 in&out R11 as	
	DIN EN 16165 _ Annex A		B in&out C as	
	DIN EN 16165 _ Annex C		≥ 36 in&out . as	
	AS/NZS 4586		P4 in&out	
Shade Variation		ANSI A137.1	V0 None _ V1 Minor V2 Low _ V3 Medium V4 Major	V2
Recommended joint		Rectified Indoor Rectified Outdoor	-	Minimum 2 mm Minimum 3 mm

It is guaranteed the compliance with the values required by norm EN 14411_Group BIA UGL. Typical Value is merely indicative, which can vary from real data, and does not have the purpose of any trading proposal.



EMAS

ISO 9001 ISO 14001

RECYCLED CONTENT

LEED

CE

CERTIF

ANTIBACTERIANO

GREENGUARD GOLD

EPD

FIRE PERFORMANCE

BE 100% CONFIDENT IN THE PRODUCTS YOU SPECIFY



“ The Grenfell Tower tragedy in London highlights the importance to specifiers of ensuring the products they specify (from flooring to cladding materials) are fire-resistant in order to conform to the building code relating to fire rating regulations. ”

TILES DO NOT REQUIRE TESTING AS THEY DO NOT CONTRIBUTE TO FIRE

In New Zealand, fire ratings are required by the Building Code to ensure that if a building is on fire, its construction materials do not significantly increase the spread or intensity of a fire. Tiles, being non-combustible, do not require testing as they do not contribute to fire. Aside from this, tiles by nature do not contain any form of petroleum-based product or wood fibres and are in essence, fire-proof and non toxic!

The building code relating to fire rating regulations and standards became mandatory from April 2013, establishing the list of products belonging to Classes A 'No contribution to fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.

WHAT YOU NEED TO KNOW:

- Because most ceramics are manufactured at over 1000 degrees celsius, they become fire-resistant and therefore an obvious choice for both commercial and residential floor and wall surfaces. For example, if a lighted cigarette is dropped on the floor, it will not do any damage to the tile. Even hot kitchen pans or skillets will not scorch or melt the surface of tile, let alone set the tile on fire.
- Tiles are non-combustible so do not catch fire, nor do they give off toxic fumes in the form of VOC's (Volatile Organic Compounds) affecting breathing, when exposed to fire.
- During the manufacture of tiles, any VOC's that may have been present in clays or binders are completely burned away which ensures the final product is inert.



A safe and simple approach with regards to Fire performance in products is to utilise tile for both **Floor** and **Wall** areas. To view latest styles and designs to suit Commercial Projects, see our tile and stone range; <https://www.tilewarehouse.co.nz/tile-stone-range/>