

# BASALTINA ANTRACITE SOFT 1000x1000



## Class 1 Building Product Information Requirements Self-Assessment

---

Product Name: BASALTINA ANTRACITE SOFT 1000x1000

Product Identifier: BASANTM1X1

Product Description: A full body porcelain tile with an soft finish and a water absorption rate of less than 0.10%.

---

## Building Code Obligations

---

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



BPIR COMPLIANT



Scope	Use
B2 Durability	See below Suitability table.
C3 Fire	The Building Code relating to fire ratings regulation and standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Not acceptable for use under D1/AS1
E3 Internal Moisture	E3 Internal Moisture (AS1 and AS2) is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed. Prevention of the creation of mould is a combination of temperature, insulation, and ventilation. Prevention of water damaging other building elements is about a complete system and installation details (i.e. Compliant and approved Waterproofing and sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information on compliant systems that meet the durability requirements of B2 that requires 15 years performance and a Producer Statement (PS3) for waterproofing.
G3 Food Preparation and Prevention from Contamination	As an Impervious and easy to clean Surface this range complies
G6 Airborne and Impact Sound	If required Tiles can form part of an acoustic system to comply with IIC and STC in conjunction with an approved third-party system.

Suitability	Residential	Light Commercial	Commercial	Industrial
Indoor Floor	✓	✓	✓	✓
Indoor Walls	✓	✓	✓	✓
Outdoor Floor	✓	-	-	-
Outdoor Cladding	✓	✓	✓	✓
Frost Resistant	✓	✓	✓	✓
Swimming Pool Submerged	✓	✓	✓	✓
Swimming Pool Surround	✓	-	-	-
Paving	-	-	-	-
Over Underfloor Heating	✓	✓	✓	✓
Commercial Kitchen Wall	✓	✓	✓	✓
Within 1.5m of a Plumbing Fixture or Fitting	✓	✓	✓	✓

Specifications	
CODE	BASANTM1X1
TILE SIZE (mm)	1000x1000
THICKNESS (mm)	6
SUITABILITY	Floor/Wall
FINISH	Soft
CLASS	Full body (through bodied) porcelain - Moderate to heavy traffic, All residential applications as well as heavy commercial.
RECTIFIED	Yes
WEIGHT (kg)	14.07
COEFFICIENT OF FRICTION	
SLIP RATING	
TILES PER BOX	2
M2 PER BOX	2.00
PATTERNS/FACES	12
COUNTRY OF ORIGIN	Italy

## Building Code Clause and Contribution

### **B2 - Durability**

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

### **C3 – Fire affecting areas beyond the source.**

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

Note – this building product is not subject to a warning or ban under section 26 of the Building Act 2004

**D1 – Access routes**

For D1 access routes, in most cases product-related compliance for access routes are slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

**E3 – Internal Moisture**

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed. Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

**G3 – Food preparation and prevention of contamination**

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious.

G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

**G6 – Airborne and Impact Sound**

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:

Tile Warehouse Approved



Importer Details:

Tile Warehouse Limited

Address: 286 Church Street, Onehunga, AKL 1061

NZBN: 9429041069448

Website: [www.tilewarehouse.co.nz](http://www.tilewarehouse.co.nz)

## SPECIFICATIONS of collection: ULTRA MARMI

[English version](#)

Supply of porcelain stoneware Ariosteal.

### 1. Product and process features

Porcelain stoneware slabs classifiable as group Bla, frost-proof slabs that resist to chemical attacks, achieved through dry-forming of high-quality mixtures made up of atomized and mixed natural raw materials (kaolin minerals, feldspars). The slabs are made mechanically resistant through a sintering process at very high temperatures.

### 2. Compliance with Standards

The material, in compliance with the requirements of European standards EN 14411 Encl. G and International standards ISO13006 Encl. G, must meet the following technical features:

ISO 10545-3 (Water absorption)  
 ISO 10545-2 (Dimensions and surface quality)  
 ISO 10545-4 (Modulus of rupture (R))  
 ISO 10545-6 (Resistance to deep abrasion)  
 ISO 10545-8 (Thermal expansion coefficient)  
 ISO 10545-9 (Thermal shock resistance)  
 ISO 10545-12 (Frost resistance)  
 ISO 10545-13 (Chemical resistance)  
 ISO 10545-14 (Stain resistance)

and it must comply with the DIN 51094 standard (Color resistance to light).

The Quality Control System implemented by the company guarantees the mentioned above features in accordance with UNI-EN-ISO 9001:2015 standards; our company also guarantees the constant respect of the laws in force concerning the health and safety of workers through the ISO 45001 management scheme.

Slabs, with a low environmental impact, obtained by pursuing policies of continuous improvement aimed at reducing the wastes of non-renewable resources by using natural raw materials that are not environmentally valuable.

Objectives achieved through the adoption of Environmental and Energy Management Systems respectively certified in accordance with the UNI-EN ISO 14001:2015 and ISO 50001:2018 standards as well as through the registration to the "ECO-MANAGEMENT" Community system according to the requirements of the EMAS Regulations.

The slabs have been checked and evaluated by an independent third-party Body which certifies their compliance to the LEED\_BREEAM, requirements and registered at Environdec, having obtained the Environmental Product Declaration EPD (type III) based on analysis of the product life cycle (s. CRADLE-TO-GRAVE approach – <https://www.environdec.com/Detail/epd1439>).

### 3. Commercial Description of the Product

<b>Company</b>	Ariosteal
<b>Collection</b>	ULTRA MARMI
<b>Product</b>	Arabescato Statuario - Bardiglio Chiaro - Bianco Calacatta - Bianco Covelano - Bianco Statuario - Calacatta Macchia Vecchia - Calacatta Viola - Crema Marfil - Crema Delicato - Fior Di Bosco - Grey Marble - Gris De Savoie - Imperial Grey - Michelangelo Altissimo - Rosso Imperiale - Statuario Altissimo - Statuario Ultra - Thassos Ultra - Travertino Santa Caterina - Verde St Denis
<b>Finish</b>	Soft
<b>Size in inch</b>	120x60 - 108x48 - 120x40 - 60x60 - 60x40 - 48x48 - 60x30 - 40x40 - 30x30 - 30x15
<b>Size in cm</b>	300x150 - 270x120 - 300x100 - 150x150 - 150x100 - 120x120 - 150x75 - 100x100 - 75x75 - 75x37,5
<b>Thickness in mm</b>	6

#### Dimensions

Materials supplied in Mono-caliber.

Nominal size in mm	Working size in mm
3000x1500 - 2700x1200 - 3000x1000 - 1500x1500 - 1500x1000 - 1200x1200 - 1500x750 - 1000x1000 - 750x750 - 750x375	3002x1500 - 2700x1200 - 3002x1000 - 1500x1500 - 1500x1000 - 1200x1200 - 1500x749 - 1000x1000 - 749x749 - 749x373,5

#### 4. Technical features

Chemical Physical	Norms	Required Standards	Average Values of Production
Water absorption	ISO 10545-3	≤ 0,5%	≤ 0,1%
Length and Width	ISO 10545-2	± 0,6%	± 0,1%
Thickness		± 5%	± 5,0%
Linearity		± 0,5%	± 0,1%
Rectangularity		± 0,5%	± 0,1%
Surface Flatness		± 0,5%	± 0,2%
Modulus of rupture (R)		ISO 10545-4	≥ 35 N/mm <sup>2</sup>
Resistance to deep abrasion	ISO 10545-6	≤ 175 mm <sup>3</sup>	140 mm <sup>3</sup>
Thermal expansion coefficient	ISO 10545-8	Test method available	6,5x10 <sup>-6</sup> °C <sup>-1</sup>
Thermal shock resistance	ISO 10545-9	Test method available	Resistant
Frost resistance	ISO 10545-12	No sample must show significant breakages or alterations	Compliant
Chemical resistance* - Household chemicals - Swimming pool salts - Low concentration of acid and alkalis - High concentration of acid and alkalis	ISO 10545-13	- Min. Class B - Manufacturer is to state classification - Test method available	A LA HA
Stain resistance	ISO 10545-14	1<X≤5	Class 5
Color resistance to light	DIN 51094	No sample should show significant color variations	No change in brightness or color
Reaction to fire	Decision 96/603 CE Test absent	---	A1 – A1 <sub>FL</sub>
Slip resistance	DIN EN 16165-ANNEX B DIN EN 16165-ANNEX A	Test method available	On request

(\*) With the exception of HYDROFLUORIC acid (HF) or its derivatives and compounds.

Date: 22/11/2023

# FIRE PERFORMANCE

## BE 100% CONFIDENT IN THE PRODUCTS YOU SPECIFY



*“ The Grenfell Tower tragedy in London highlights the importance to specifiers of ensuring the products they specify (from flooring to cladding materials) are fire-resistant in order to conform to the building code relating to fire rating regulations. ”*

## TILES DO NOT REQUIRE TESTING AS THEY DO NOT CONTRIBUTE TO FIRE

In New Zealand, fire ratings are required by the Building Code to ensure that if a building is on fire, its construction materials do not significantly increase the spread or intensity of a fire. Tiles, being non-combustible, do not require testing as they do not contribute to fire. Aside from this, tiles by nature do not contain any form of petroleum-based product or wood fibres and are in essence, fire-proof and non toxic!

**The building code relating to fire rating regulations and standards became mandatory from April 2013**, establishing the list of products belonging to Classes A 'No contribution to fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.

### WHAT YOU NEED TO KNOW:

- Because most ceramics are manufactured at over 1000 degrees celsius, they become fire-resistant and therefore an obvious choice for both commercial and residential floor and wall surfaces. For example, if a lighted cigarette is dropped on the floor, it will not do any damage to the tile. Even hot kitchen pans or skillets will not scorch or melt the surface of tile, let alone set the tile on fire.
- Tiles are non-combustible so do not catch fire, nor do they give off toxic fumes in the form of VOC's (Volatile Organic Compounds) affecting breathing, when exposed to fire.
- During the manufacture of tiles, any VOC's that may have been present in clays or binders are completely burned away which ensures the final product is inert.



A safe and simple approach with regards to Fire performance in products is to utilise tile for both **Floor** and **Wall** areas. To view latest styles and designs to suit Commercial Projects, see our tile and stone range; <https://www.tilewarehouse.co.nz/tile-stone-range/>