

SILVER TRAV. METAL MIX FINGERS HONED 300x300



Class 1 Building Product Information Requirements Self-Assessment

Product Name: SILVER TRAV. METAL MIX FINGERS HONED 300x300

Product Identifier: SILTRAMFM30

Product Description: A metal capped ceramic mosaic with an honed finish and a water absorption rate of less than 0.00%.

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



BPIR COMPLIANT



Scope	Use
B2 Durability	See below Suitability table.
C3 Fire	The Building Code relating to fire ratings regulation and standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Not acceptable for use under D1/AS1
E3 Internal Moisture	E3 Internal Moisture (AS1 and AS2) is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed. Prevention of the creation of mould is a combination of temperature, insulation, and ventilation. Prevention of water damaging other building elements is about a complete system and installation details (i.e. Compliant and approved Waterproofing and sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information on compliant systems that meet the durability requirements of B2 that requires 15 years performance and a Producer Statement (PS3) for waterproofing.
G3 Food Preparation and Prevention from Contamination	As an Impervious and easy to clean Surface this range complies
G6 Airborne and Impact Sound	If required Tiles can form part of an acoustic system to comply with IIC and STC in conjunction with an approved third-party system.

Suitability	Residential	Light Commercial	Commercial	Industrial
Indoor Floor	-	-	-	-
Indoor Walls	✓	✓	✓	✓
Outdoor Floor	-	-	-	-
Outdoor Cladding	✓	✓	✓	✓
Frost Resistant	✓	✓	✓	✓
Swimming Pool Submerged	-	-	-	-
Swimming Pool Surround	-	-	-	-
Paving	-	-	-	-
Over Underfloor Heating	-	-	-	-
Commercial Kitchen Wall	✓	✓	✓	✓
Within 1.5m of a Plumbing Fixture or Fitting	✓	✓	✓	✓

Specifications	
CODE	SILTRAMFM30
TILE SIZE (mm)	300x300
THICKNESS (mm)	10
SUITABILITY	Wall
FINISH	Honed
CLASS	Mosaic - Suitable for walls only and unsuitable for use on floors.
RECTIFIED	Yes
WEIGHT (kg)	1.45
COEFFICIENT OF FRICTION	
SLIP RATING	
TILES PER BOX	11
M2 PER BOX	0.00
PATTERNS/FACES	
COUNTRY OF ORIGIN	China

Building Code Clause and Contribution

B2 - Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source.

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

Note – this building product is not subject to a warning or ban under section 26 of the Building Act 2004

For D1 access routes, in most cases product-related compliance for access routes are slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed.

Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious.

G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:

Tile Warehouse Approved



Importer Details:

Tile Warehouse Limited

Address: 286 Church Street, Onehunga, AKL 1061

NZBN: 9429041069448

Website: www.tilewarehouse.co.nz



中国认可
国际互认
检测

国家陶瓷及水暖卫浴产品质量监督检验中心

检验报告

No:C07-CJ1700


表号: QR-049-01

共2页第1页

产品名称 型号、规格 商标、等级	水晶玻璃马赛克 23mm×23mm×8.0mm	生产日期 或批号	-----/-----
		样品编号	-
委托单位	佛山市玛邦装饰材料有限公司	检验类别	委托检验
委托单位地址	广东省佛山市丹灶镇罗行田心工业区	样品数量/ 来样方式	1箱/送样
生产单位 (委托方提供)	佛山市玛邦装饰材料有限公司	接样日期	2020年03月20日
生产单位地址 (委托方提供)	广东省佛山市丹灶镇罗行田心工业区	接样人	李冬平
样品特征 及状态	块状	检验日期	2020年03月21日至 2020年04月03日
检验依据	GB/T 7697-1996 《玻璃马赛克》		
检 验 结 论	共检8项, 所检项目符合GB/T 7697-1996标准要求, 本次抽检合格		
备 注	 二〇二〇年四月十一日 复印报告未重盖红色“检验专用章”无效		

批准: 曹阳 

审核: 

主检: 

检验单位地址: 广东省佛山市南海区狮山镇科技西路2号电话: 0757-88735166 邮箱: nccs0757@163.com



中国认可
国际互认
检测

180002113069 (2013)国认监认字(400)号
国家陶瓷及水暖卫浴产品质量监督检验中心

检验报告

No.:C07-CJ1700

表号: QR-049-02

共2页第2页

序号	检测项目	单位符号	标准要求		检测结果	判定
1	单块尺寸及偏差	mm	边长	23±0.5	22.8~23.5	合格
		mm	厚度	8±0.4	8.0~8.2	
2	线路及偏差	mm	2.0±0.6		1.8~2.2	合格
3	联长	mm	300±2.0		299.4~300.4	合格
4	外观质量	—	应符合标准中5.2条表3中优等品的要求		符合	合格
5	色差	—	目测基本一致		符合	合格
6	铺贴衬材的粘结性	—	不允许有马赛克脱落		符合	合格
7	热稳定性	—	90℃ (30min)至18~25℃ (10min)循环3次,全部试样均无裂纹和破损		符合	合格
8	化学稳定性	%	1mol/L盐酸溶液, 100℃, 4h, K≥99.90		K=99.97	合格
			1mol/L硫酸溶液, 100℃, 4h, K≥99.93		K=99.96	
			1mol/L氢氧化钠溶液, 100℃, 4h, K≥99.88		K=99.97	
			蒸馏水, 100℃, 4h, K≥99.96		K=99.99	

(以下空白)

FIRE PERFORMANCE

BE 100% CONFIDENT IN THE PRODUCTS YOU SPECIFY



“ The Grenfell Tower tragedy in London highlights the importance to specifiers of ensuring the products they specify (from flooring to cladding materials) are fire-resistant in order to conform to the building code relating to fire rating regulations. ”



TILES DO NOT REQUIRE TESTING AS THEY DO NOT CONTRIBUTE TO FIRE

In New Zealand, fire ratings are required by the Building Code to ensure that if a building is on fire, its construction materials do not significantly increase the spread or intensity of a fire. Tiles, being non-combustible, do not require testing as they do not contribute to fire. Aside from this, tiles by nature do not contain any form of petroleum-based product or wood fibres and are in essence, fire-proof and non toxic!

The building code relating to fire rating regulations and standards became mandatory from April 2013, establishing the list of products belonging to Classes A 'No contribution to fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.

WHAT YOU NEED TO KNOW:

- Because most ceramics are manufactured at over 1000 degrees celsius, they become fire-resistant and therefore an obvious choice for both commercial and residential floor and wall surfaces. For example, if a lighted cigarette is dropped on the floor, it will not do any damage to the tile. Even hot kitchen pans or skillets will not scorch or melt the surface of tile, let alone set the tile on fire.
- Tiles are non-combustible so do not catch fire, nor do they give off toxic fumes in the form of VOC's (Volatile Organic Compounds) affecting breathing, when exposed to fire.
- During the manufacture of tiles, any VOC's that may have been present in clays or binders are completely burned away which ensures the final product is inert.



A safe and simple approach with regards to Fire performance in products is to utilise tile for both **Floor** and **Wall** areas. To view latest styles and designs to suit Commercial Projects, see our tile and stone range; <https://www.tilewarehouse.co.nz/tile-stone-range/>