SLIP RESISTANCE TEST REPORT

Client: Tile Warehouse Tested By: Dave Cockerton

Client's Reference: 7369 Date: 10 May 2016

DESCRIPTION OF SAMPLE

Manufacturer: Del Conca Material Type: Porcelain Common Name: Natural Black – HNT-8 Surface Type: Structured

Specimen Size: 600 x 600mm Colour: Natural Black – HNT-8

No. of Specimens Tested. 5 Surface Coating: Nil

METHOD

Tests were carried out in accordance with AS/NZS 4586:2004 (Incorporating Amendment No 1) Slip Resistance of Pedestrian Surfaces, Part 1- Requirements, Appendix A "Method for the Measurement of the Coefficient of friction of Wet Surfaces".

Type of Test: **Wet**Air Temperature: °C18

Location of Test: 19b Neil Park Drive
East Tamaki

RESULTS			
Specimen No.	Dilution Ratio	Dwell Time	Mean Coefficient of Friction
one			0.56
two			0.64
three			0.55
four			0.60
five			0.64

SAMPLE MEAN COEFFICIENT OF FRICTION: 0.60

REQUIREMENTS

<u>Horizontal Surfaces</u>: When tested in accordance with the method set out in Appendix A, the pedestrian surface shall have a mean coefficient of friction of not less than **0.40** and no specimen in that sample shall be less than **0.35**.

COMMENTS:

SAFETY STEP (NZ) LTD

THE ULTIMATE IN ANTI-SLIP AND WAY FINDING SYSTEMS